

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	MODB

1.10.3. Cluster ID

ID	Name
n/a	Mode Base

1.10.4. Features

This cluster SHALL support the FeatureMap bitmap attribute as defined below.

Bit	Code	Feature	Summary
0	DEPONOFF	OnOff	Dependency with the OnOff cluster

1.10.4.1. OnOff Feature

This feature creates a dependency between an OnOff cluster instance and this cluster instance on the same endpoint. See [OnMode](#) for more information.

1.10.5. Data Types

1.10.5.1. ModeTagStruct Type

A Mode Tag is meant to be interpreted by the client for the purpose the cluster serves.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	MfgCode	vendor-id	desc				O
1	Value	enum16	all				M

1.10.5.1.1. MfgCode Field

If the MfgCode field exists, the Value field SHALL be in the manufacturer-specific value range (see [Section 1.10.8, “Mode Namespace”](#)).

This field SHALL indicate the manufacturer’s VendorID and it SHALL determine the meaning of the Value field.

The same manufacturer code and mode tag value in separate cluster instances are part of the same namespace and have the same meaning. For example: a manufacturer tag meaning "pinch" can be used both in a cluster whose purpose is to choose the amount of sugar, or in a cluster whose purpose is to choose the amount of salt.