

1.16.8.3.3. Reply Field

This field SHALL indicate a user-provided reply to the message. If there was no reply, or the message did not have the [ReplyRequired](#) bit set, this field SHALL be null.

1.16.8.3.4. FutureMessagesPref Field

This field SHALL indicate a user-provided preference for the delivery of similar messages in the future. A null value SHALL indicate no change in preference.

1.17. Service Area Cluster

This cluster provides an interface for controlling the areas where a device should operate, for reporting the status at each area, and for querying the current area.

The device MAY operate at one area at a time, as in the case of a mobile device, such as a robot. Other devices MAY operate at (service) multiple areas simultaneously, as in the case of a sensor that can monitor multiple areas. This cluster specification uses the term "operate" to describe both the operating and servicing actions, regardless of the device type.

The cluster allows the client to select one or more areas on the server, to indicate where the device SHOULD attempt to operate. An area is one of a list of options that MAY be presented by a client for a user choice, or understood by the client, via the semantic data of the area.

The area semantic data is a combination of semantic tags, indicating one or more of the following: the building floor, area type, landmark, and relative position.

1.17.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision
2	Rename InitialTimeEstimate to EstimatedTime

1.17.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	SEAR

1.17.3. Cluster ID

ID	Name
0x0150	Service Area