

1.17.5.2.1. LocationInfo Field

This field SHALL indicate the name of the area, floor number and/or area type.

A few examples are provided below.

- An area can have LocationInfo's LocationName field set to "blue room", and the AreaType field set to the ID of a "Living Room" semantic tag. Clients wishing to direct the device to operate in (or service) the living room can use this area.
- An area can have LocationInfo set to null, the LandmarkInfo's LandmarkTag field set to the ID of the "Table" landmark semantic tag, and the RelativePositionTag field set to the ID of the "Under" position semantic tag. With such an area indication, the client can request the device to operate in (or service) the area located under the table.

1.17.5.2.2. LandmarkInfo Field

This field SHALL indicate an association with a landmark. A value of null indicates that the information is not available or known. For example, this may indicate that the area refers to a zone next to a table.

If this field is not null, that indicates that the area is restricted to the zone where the landmark is located, as indicated by the LandmarkTag and, if not null, by the RelativePositionTag fields, rather than to the entire room or floor where the landmark is located, if those are indicated by the LocationInfo field.

1.17.5.3. MapStruct Type

This is a struct representing a map.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	MapID	uint32			MS		M
1	Name	string	max 64		MS		M

1.17.5.3.1. MapID Field

This field SHALL represent the map's identifier.

1.17.5.3.2. Name Field

This field SHALL represent a human understandable map description.

For example: "Main Floor", or "Second Level".

1.17.5.4. AreaStruct Type

This is a struct representing an area known to the server.