

Revision	Description
3	New data model format and notation
4	Remove nullable from PhysicalContact delay attributes and ability to not report transitions
5	Rework to add modalities: radar-, ambient-sensing- and vision-based sensors; add sensitivity setting (via co-located BooleanStateConfiguration cluster on same end-point); add new attribute for tuning the sensor's reporting; add event Occupancy-Changed; add N quality for HoldTime and other timing attributes; describe how to accommodate legacy clients

2.7.1.1. Backward compatibility

With the introduction of new sensor modalities in cluster revision 5, the indication for those modalities SHALL be done using feature bits. Indication of those new modalities is not feasible via the legacy attributes OccupancySensorType and OccupancySensorTypeBitmap. Servers SHALL set these attributes for backward compatibility with clients implementing a cluster revision ≤ 4 as described in [OccupancySensorType and OccupancySensorTypeBitmap Attributes](#). Clients implementing a cluster revision ≥ 5 SHOULD use the server's ClusterRevision attribute, and SHOULD ignore these legacy attributes.

With the same revision 5, the attribute HoldTime (along with the HoldTimeLimits) is used to determine the reporting when occupancy is no longer detected. This replaces the 9 legacy attributes PIROccupiedToUnoccupiedDelay through PhysicalContactUnoccupiedToOccupiedThreshold. Servers MAY use the applicable attributes from this set of legacy attributes if and only if HoldTime is supported (see Attribute table and [the corresponding explanation](#) for details on conformance).

For the case of a server which supports none of the modalities supported in ClusterRevision ≤ 4 (i.e. none of PIR, US and PHY), specific mappings for the legacy attributes OccupancySensorType and OccupancySensorTypeBitmap are provided [below](#), representing this sensor as a PIR sensor for best-effort backward compatibility. For this case, the legacy timing attributes linked to PIR (i.e. PIROccupiedToUnoccupiedDelay through PIRUnoccupiedToOccupiedThreshold) apply.

2.7.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	OCC

2.7.3. Cluster ID

Cluster ID	Cluster Name
0x0406	Occupancy Sensing

2.7.4. Features

This cluster SHALL support the FeatureMap bitmap attribute as defined below. For sensor devices implementing multiple modalities, please see the guidance provided in the Occupancy Sensor