

2.7.5.1.1. Occupied Bit

If this bit is set, it SHALL indicate the occupied state else if the bit if not set, it SHALL indicate the unoccupied state.

2.7.5.2. OccupancySensorTypeBitmap Type

This data type is derived from map8.

Bit	Name	Summary	Conformance
0	PIR	Indicates a passive infrared sensor.	M
1	Ultrasonic	Indicates a ultrasonic sensor.	M
2	PhysicalContact	Indicates a physical contact sensor.	M

NOTE

This enum is as defined in ClusterRevision 4 and its definition SHALL NOT be extended; the feature flags provide the sensor modality (or modalities) for later cluster revisions. See [Backward Compatibility section](#).

2.7.5.3. OccupancySensorTypeEnum Type

This data type is derived from enum8.

Value	Name	Summary	Conformance
0	PIR	Indicates a passive infrared sensor.	M
1	Ultrasonic	Indicates a ultrasonic sensor.	M
2	PIRAndUltrasonic	Indicates a passive infrared and ultrasonic sensor.	M
3	PhysicalContact	Indicates a physical contact sensor.	M

NOTE

This enum is as defined in ClusterRevision 4 and its definition SHALL NOT be extended; the feature flags provide the sensor modality (or modalities) for later cluster revisions. See [Backward Compatibility section](#).

2.7.5.4. HoldTimeLimitsStruct Type

This structure provides information on the server's supported values for the HoldTime attribute.