

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Hold-TimeMin	uint16	min 1				M
1	Hold-TimeMax	uint16	min maxOf(HoldTimeMin, 10)				M
2	Hold-TimeDefault	uint16	Hold-TimeMin to Hold-TimeMax				M

2.7.5.4.1. HoldTimeMin Field

This field SHALL specify the minimum value of the server's supported value for the HoldTime attribute, in seconds.

2.7.5.4.2. HoldTimeMax Field

This field SHALL specify the maximum value of the server's supported value for the HoldTime attribute, in seconds.

2.7.5.4.3. HoldTimeDefault Field

This field SHALL specify the (manufacturer-determined) default value of the server's HoldTime attribute, in seconds. This is the value that a client who wants to reset the settings to a valid default SHOULD use.

2.7.6. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	Occupancy	OccupancyBitmap	0 to 1	P		R V	M
0x0001	OccupancySensorType	OccupancySensorTypeEnum	desc	F		R V	M, D
0x0002	OccupancySensorTypeBitmap	OccupancySensorTypeBitmap	0 to 7	F		R V	M, D