

2.12.7.1.2. EnergyExported Field

This field SHALL be the value of [CumulativeEnergyExported](#) attribute at the timestamp indicated in its [EndTimestamp](#) field, [EndSystemtime](#) field, or both.

2.12.7.2. PeriodicEnergyMeasured Event

This event SHALL be generated when the server reaches the end of a reporting period for imported energy, exported energy, or both.

The data of this event SHALL contain the following information:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	EnergyImported	EnergyMeasurementStruct				PERE & IMPE
1	EnergyExported	EnergyMeasurementStruct				PERE & EXPE

2.12.7.2.1. EnergyImported Field

This field SHALL be the value of [PeriodicEnergyImported](#) attribute at the timestamp indicated in its [EndTimestamp](#) field, [EndSystemtime](#) field, or both.

2.12.7.2.2. EnergyExported Field

This field SHALL be the value of [PeriodicEnergyExported](#) attribute at the timestamp indicated in its [EndTimestamp](#) field, [EndSystemtime](#) field, or both.

2.13. Electrical Power Measurement Cluster

This cluster provides a mechanism for querying data about electrical power as measured by the server.

2.13.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision
2	Changed reactive and apparent power fields to use new data types
3	Changed range of apparent current field to allow negative apparent current