

SHALL use the system time fields to specify the measurement period and observation times.

A server which has determined the time in UTC SHALL use the timestamp fields to specify the measurement period and observation times. Such a server MAY also include the systime fields to indicate how many seconds had passed since boot for a given timestamp; this allows for client-side resolution of UTC time for previous reports that only included systime.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	MeasurementType	MeasurementTypeEnum					M
1	Min	int64	-2^{62} to 2^{62}				M
2	Max	int64	-2^{62} to 2^{62}				M
3	StartTimeStamp	epoch-s					EndTimeStamp
4	EndTimeStamp	epoch-s	min (StartTimeStamp + 1)				desc
5	MinTimeStamp	epoch-s					EndTimeStamp
6	MaxTimeStamp	epoch-s	min (MinTimeStamp + 1)				EndTimeStamp
7	StartSystime	systime-ms					EndSystime
8	EndSystime	systime-ms	min (StartSystime + 1)				desc
9	MinSystime	systime-ms					EndSystime
10	MaxSystime	systime-ms	min (MinSystime + 1)				EndSystime

2.13.5.3.1. MeasurementType Field

This field SHALL be the type of measurement for the range provided.

2.13.5.3.2. Min Field

This field SHALL be the smallest measured value for the associated measurement over either the period between [StartTimeStamp](#) and [EndTimeStamp](#), or the period between [StartSystime](#) and [EndSystime](#), or both.