

8. ColorTemperatureMireds (null)

9. EnhancedColorMode

Since there is a direct relation between ColorTemperatureMireds and XY, color temperature, if supported, is stored as XY in the scenes table.

Attributes in the scene table that are not supported by the device (according to the FeatureMap attribute) SHALL be present in the scene table but ignored.

If the Scenes Management cluster server is implemented on the same endpoint, and the cluster revision is 6 or above, then all extension fields in the list above, including up to EnhancedColorMode (item 9), SHALL be present in the extension fields set for a Scene to be considered valid. This disambiguates the color mode used within the Scene.

3.2.7.2. CurrentHue Attribute

The CurrentHue attribute contains the current hue value of the light. It is updated as fast as practical during commands that change the hue.

The hue in degrees SHALL be related to the CurrentHue attribute by the relationship:

$$\text{Hue} = \text{"CurrentHue"} * 360 / 254$$

where CurrentHue is in the range from 0 to 254 inclusive.

Changes to this attribute SHALL only be marked as reportable in the following cases:

- At most once per second or
- At the end of the movement/transition.

3.2.7.3. CurrentSaturation Attribute

This attribute SHALL indicate the current saturation value of the light. It is updated as fast as practical during commands that change the saturation.

The saturation (on a scale from 0.0 to 1.0) SHALL be related to the CurrentSaturation attribute by the relationship:

$$\text{Saturation} = \text{"CurrentSaturation"} / 254$$

where CurrentSaturation is in the range from 0 to 254 inclusive.

Changes to this attribute SHALL only be marked as reportable in the following cases:

- At most once per second or
- At the end of the movement/transition.