

3.2.7.7. DriftCompensationAttribute

This attribute SHALL indicate what mechanism, if any, is in use for compensation for color/intensity drift over time.

3.2.7.8. CompensationTextAttribute

This attribute SHALL contain a textual indication of what mechanism, if any, is in use to compensate for color/intensity drift over time.

3.2.7.9. ColorTemperatureMiredsAttribute

This attribute SHALL indicate a **scaled inverse** of the current value of the color temperature. The unit of ColorTemperatureMireds is the mired (micro reciprocal degree), a.k.a. mirek (micro reciprocal kelvin). It is updated as fast as practical during commands that change the color.

Changes to this attribute SHALL only be marked as reportable in the following cases:

- At most once per second or
- At the end of the movement/transition.

The color temperature value in kelvins SHALL be related to the ColorTemperatureMireds attribute in mired by the relationship

$$\text{"Color temperature [K]} = \text{"1,000,000"} / \text{"ColorTemperatureMireds"}$$

where ColorTemperatureMireds is in the range from 1 to 65279 inclusive, giving a color temperature range from 1,000,000 K to 15.32 K.

If this attribute is implemented then the ColorMode attribute SHALL also be implemented.

3.2.7.10. ColorModeAttribute

This attribute SHALL indicate which attributes are currently determining the color of the device.

The value of the ColorMode attribute cannot be written directly - it is set upon reception of any command in section [Commands](#) to the appropriate mode for that command.

3.2.7.11. OptionsAttribute

This attribute SHALL indicate a bitmap that determines the default behavior of some cluster commands. Each command that is dependent on the Options attribute SHALL first construct a temporary Options bitmap that is in effect during the command processing. The temporary Options bitmap has the same format and meaning as the Options attribute, but includes any bits that may be overridden by command fields.

This attribute is meant to be changed only during commissioning.

Below is the format and description of the Options attribute and temporary Options bitmap and the effect on dependent commands.