

- f. If the **PresetHandle** field is present, but the associated **ScheduleTypeStruct** does not have the **SupportsPresets** bit set, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - g. If the **PresetHandle** field is present, but after applying all pending changes, the **Presets** attribute would not contain a **PresetStruct** whose **PresetHandle** field matches the value of the **PresetHandle** field, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - h. If the **Name** is set, but the associated **ScheduleTypeStruct** does not have the **SupportsNames** bit set, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - i. For all **transitions** in all **schedules** in the write request:
 - i. If the **PresetHandle** field is present, but the **ScheduleTypeStruct** matching the value of the **SystemMode** field on the encompassing **ScheduleStruct** does not have the **SupportsPresets** bit set, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - j. If the **PresetHandle** field is present, but after applying all pending changes, the **Presets** attribute would not contain a **PresetStruct** whose **PresetHandle** field matches the value of the **PresetHandle** field, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - i. If the **SystemMode** field is present, but the **ScheduleTypeStruct** matching the value of the **SystemMode** field on the encompassing **ScheduleStruct** does not have the **SupportsSetpoints** bit set, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - ii. If the **SystemMode** field is has a value of **SystemModeOff**, but the **ScheduleTypeStruct** matching the value of the **SystemMode** field on the encompassing **ScheduleStruct** does not have the **SupportsOff** bit set, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - k. If the **HeatingSetpoint** field is present, but the **ScheduleTypeStruct** matching the value of the **SystemMode** field on the encompassing **ScheduleStruct** does not have the **SupportsSetpoints** bit set, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - l. If the **CoolingSetpoint** field is present, but the **ScheduleTypeStruct** matching the value of the **SystemMode** field on the encompassing **ScheduleStruct** does not have the **SupportsSetpoints** bit set, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 2. If appending the received **ScheduleStruct** to the pending list of Schedules would cause the total number of pending **schedules** to exceed the value of the **NumberOfSchedules** attribute, a response with the status code **RESOURCE_EXHAUSTED** SHALL be returned.
 3. If appending the received **ScheduleStruct** to the pending list of Schedules would cause the total number of pending **schedules** whose **SystemMode** field matches the appended schedule's **SystemMode** field to exceed the value of the **NumberOfSchedules** field on the **ScheduleTypeStruct** whose **SystemMode** field matches the appended schedule's **SystemMode** field, a response with the status code **RESOURCE_EXHAUSTED** SHALL be returned.
 4. Otherwise, the write SHALL be pended until receipt of a commit request, and the attribute status SHALL be **SUCCESS**.
 - a. If the **BuiltIn** field is null:
 - i. If there is a **ScheduleStruct** in the current value with a matching **ScheduleHandle** field,