

4.3.10.3. GetWeeklySchedule Command

This command will return the weekly schedule for the values provided.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	DaysToReturn	Schedule-DayOfWeek-Bitmap	desc			M
1	ModeToReturn	Schedule-ModeBitmap	desc			M

4.3.10.3.1. DaysToReturn Field

This field SHALL indicate the number of days the client would like to return the setpoint values for and could be any combination of single days or the entire week.

4.3.10.3.2. ModeToReturn Field

This field SHALL indicate the mode the client would like to return the set point values for and could be any combination of heat only, cool only or heat & cool.

4.3.10.3.3. Effect on Receipt

Upon receipt, the unit SHOULD send in return the Get Weekly Schedule Response command. The Days to Return and Mode to Return fields are defined as bitmask for the flexibility to support multiple days and multiple modes within one command. If thermostat cannot handle incoming command with multiple days and/or multiple modes within one command, it SHALL send default response of INVALID_COMMAND in return.

4.3.10.4. GetWeeklyScheduleResponse Command

This command has the same payload format as the Set Weekly Schedule.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	NumberOfTransitionsForSequence	uint8	all			M
1	DayOfWeekForSequence	Schedule-DayOfWeek-Bitmap	desc			M
2	ModeForSequence	Schedule-ModeBitmap	desc			M