

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0083	AliroExpedited-TransactionSupported-ProtocolVersions	list[octstr]	max 16[2]	F		R A	ALIRO
0x0084	AliroGroupResolvingKey	octstr	16	X		R A	ALBU
0x0085	AliroSupported-BLEUWBP-ProtocolVersions	list[octstr]	max 16[2]	F		R A	ALBU
0x0086	AliroBLEAdvertisingVersion	uint8	all	F		R A	ALBU
0x0087	NumberOfAliroCredentialIssuerKeysSupported	uint16	all	F		R V	ALIRO
0x0088	NumberOfAliroEndpointKeysSupported	uint16	all	F		R V	ALIRO

5.2.9.1. LockState Attribute

This attribute may be NULL if the lock hardware does not currently know the status of the locking mechanism. For example, a lock may not know the LockState status after a power cycle until the first lock actuation is completed.

The Not Fully Locked value is used by a lock to indicate that the state of the lock is somewhere between Locked and Unlocked so it is only partially secured. For example, a deadbolt could be partially extended and not in a dead latched state.

5.2.9.2. LockType Attribute

This attribute SHALL indicate the type of door lock as defined in [LockTypeEnum](#).