

5.2.9.3. ActuatorEnabled Attribute

This attribute SHALL indicate if the lock is currently able to (Enabled) or not able to (Disabled) process remote Lock, Unlock, or Unlock with Timeout commands.

This attribute has the following possible values:

Boolean Value	Summary
0	Disabled
1	Enabled

5.2.9.4. DoorState Attribute

This attribute SHALL indicate the current door state as defined in [DoorStateEnum](#).

This attribute SHALL be null only if an internal error prevents the retrieval of the current door state.

5.2.9.5. DoorOpenEvents Attribute

This attribute SHALL hold the number of door open events that have occurred since it was last zeroed.

5.2.9.6. DoorClosedEvents Attribute

This attribute SHALL hold the number of door closed events that have occurred since it was last zeroed.

5.2.9.7. OpenPeriod Attribute

This attribute SHALL hold the number of minutes the door has been open since the last time it transitioned from closed to open.

5.2.9.8. NumberOfTotalUsersSupported Attribute

This attribute SHALL indicate the number of total users supported by the lock.

5.2.9.9. NumberOfPINUsersSupported Attribute

This attribute SHALL indicate the number of PIN users supported.

5.2.9.10. NumberOfRFIDUsersSupported Attribute

This attribute SHALL indicate the number of RFID users supported.

5.2.9.11. NumberOfWeekDaySchedulesSupportedPerUser Attribute

This attribute SHALL indicate the number of configurable week day schedule supported per user.