

Use Case	Description
Modify an existing user record	• OperationType SHALL be set to Modify. • UserIndex value SHALL be set for a user record with UserType NOT set to Available. • UserName SHALL be null if modifying a user record that was not created by the accessing fabric. • INVALID_COMMAND SHALL be returned if UserName is not null and the accessing fabric index doesn't match the CreatorFabricIndex in the user record otherwise UserName SHALL be set to the value provided in the user record. • UserUniqueID SHALL be null if modifying the user record that was not created by the accessing fabric. • INVALID_COMMAND SHALL be returned if UserUniqueID is not null and the accessing fabric index doesn't match the CreatorFabricIndex in the user record otherwise UserUniqueID SHALL be set to the value provided in the user record. • UserStatus MAY be null causing no change to UserStatus in user record otherwise UserStatus SHALL be set to the value provided in the user record. • UserType MAY be null causing no change to UserType in user record otherwise UserType SHALL be set to the value provided in the user record. • CredentialRule MAY be null causing no change to CredentialRule in user record otherwise CredentialRule SHALL be set to the value provided in the user record. CreatorFabricIndex SHALL NOT be changed in the user record. LastModifiedFabricIndex in the new user record SHALL be set to the accessing fabric index. A LockUserChange event SHALL be generated after successfully modifying a user.

Return status is a global status code or a cluster-specific status code from the [Status Codes](#) table and