

- **INVALID_COMMAND**, if one or more fields violate constraints or are invalid.
- **INVALID_COMMAND**, if the **CredentialIndex** in the **Credential** provided exceeds the number of credentials of the provided **CredentialType** supported by the lock.
- **INVALID_COMMAND**, if **OperationType** is **Modify** and **UserIndex** points to an available slot.

5.2.10.37.2. **UserIndex** Field

This field SHALL indicate the user index that was created with the new credential. If the status being returned is not success then this SHALL be null. This SHALL be null if **OperationType** was **Modify**; if the **OperationType** was **Add** and a new User was created this SHALL NOT be null and SHALL provide the **UserIndex** created. If the **OperationType** was **Add** and an existing User was associated with the new credential then this SHALL be null.

5.2.10.37.3. **NextCredentialIndex** Field

This field SHALL indicate the next available index in the database for the credential type set, which is useful for quickly identifying available credential slots in the database. This SHALL NOT be null if there is at least one available entry after the requested credential index in the corresponding database and SHALL be null if there are no more available entries. The **NextCredentialIndex** reported SHALL NOT exceed the maximum number of credentials for a particular credential type.

5.2.10.38. **GetCredentialStatus** Command

Retrieve the status of a particular credential (e.g. PIN, RFID, Fingerprint, etc.) by index.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Credential	Credential-Struct				M

An **InvokeResponse** command SHALL be sent with an appropriate error (e.g. **FAILURE**, **INVALID_COMMAND**, etc.) as needed otherwise the [GetCredentialStatusResponse](#) command SHALL be sent implying a status of **SUCCESS**.

5.2.10.38.1. **Credential** Field

This field SHALL contain a credential structure that contains the [CredentialTypeEnum](#) and the credential index (if applicable or 0 if not) to retrieve the status for.

5.2.10.39. **GetCredentialStatusResponse** Command

Returns the status for the specified credential.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	CredentialExists	bool	all			M