

database and SHALL be null if there are no more occupied entries. The NextCredentialIndex reported SHALL NOT exceed the maximum number of credentials for a particular credential type.

5.2.10.39.6. CredentialData Field

This field SHALL indicate the credential data for the requested user index.

If the CredentialType in the GetCredentialStatus command was not AliroCredentialIssuerKey, AliroEvictableEndpointKey, or AliroNonEvictableEndpointKey, this field SHALL NOT be included.

Otherwise, if CredentialExists is false this field SHALL be null.

Otherwise, the value of this field SHALL be the value of the relevant credential, as a 65-byte uncompressed elliptic curve public key as defined in section 2.3.3 of [SEC 1](#).

NOTE

Since the Aliro credentials are public keys, there is no security risk in allowing them to be read. Possession of the credential octet string does not allow operating the lock.

5.2.10.40. ClearCredential Command

Clear one, one type, or all credentials except ProgrammingPIN credential.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Credential	Credential-Struct	desc	X		M

Fields used for different use cases:

Use Case	Description
Clear a single credential	- CredentialType in Credential structure SHALL be set to the credential type to be cleared. - CredentialType in Credential structure SHALL NOT be set to ProgrammingPIN. - CredentialIndex in Credential structure SHALL be set to the credential index to be cleared. A LockUserChange event SHALL be generated after successfully clearing a credential.