

Use Case	Description
Clear all credentials of one type	• CredentialType in Credential structure SHALL be set to the credential type to be cleared. • CredentialType in Credential structure SHALL NOT be set to ProgrammingPIN. • CredentialIndex in Credential structure SHALL be set to 0xFFFF to indicate all credentials of that type SHALL be cleared. A single LockUserChange event SHALL be generated after successfully clearing credentials. This event SHALL have DataIndex set to the CredentialIndex in the Credential structure.
Clear all credentials of all types	• Credential field SHALL be null. The ProgrammingPIN credential SHALL NOT be cleared. For each credential type cleared, a LockUserChange event with the corresponding LockDataType SHALL be generated. This event SHALL have DataIndex set to 0xFFFF.

For each credential cleared whose user doesn't have another valid credential, the corresponding user record SHALL be reset back to default values and its UserStatus value SHALL be set to Available and UserType value SHALL be set to UnrestrictedUser and all schedules SHALL be cleared. In this case a LockUserChange event SHALL be generated for the user being cleared.

Return status SHALL be one of the following values:

Name	Summary
SUCCESS	Clearing the requested credential was successful.
FAILURE	Some unexpected internal error occurred clearing the requested credential.
INVALID_COMMAND	One or more fields violate constraints or are invalid.

5.2.10.40.1. Credential Field

This field SHALL contain a credential structure that contains the [CredentialTypeEnum](#) and the credential index (0xFFFF for all credentials or 0 if not applicable) to clear. This SHALL be null if clearing all credential types otherwise it SHALL NOT be null.