

ID	Name	Priority	Quality	Access	Conformance
0x02	LockOperation	desc		V	M
0x03	LockOperationError	desc		V	M
0x04	LockUserChange	INFO		V	USR

The Events specified in this cluster are not intended to define the user experience. The events are only intended to define the metadata format used to notify any nodes that have subscribed for updates.

If the DoorState reported in the DoorStateChange event is not DoorClosed then the priority SHALL be CRITICAL; otherwise it MAY be INFO.

If the LockOperationType reported in the LockOperation event is Unlock or ForcedUserEvent then the priority SHALL be CRITICAL; otherwise it MAY be INFO.

If the OperationError reported in the LockOperationError event is DisabledUserDenied or the LockOperationType is Lock the priority SHALL be CRITICAL; otherwise it MAY be INFO.

5.2.11.1. DoorLockAlarm Event

The door lock server provides several alarms which can be sent when there is a critical state on the door lock. The alarms available for the door lock server are listed in [AlarmCodeEnum](#).

The data of this event SHALL contain the following information:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	AlarmCode	AlarmCodeEnum	all			M

5.2.11.1.1. AlarmCode Field

This field SHALL indicate the alarm code of the event that has happened.

5.2.11.2. DoorStateChange Event

The door lock server sends out a DoorStateChange event when the door lock door state changes.

The data of this event SHALL contain the following information:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	DoorState	DoorStateEnum	all			M