

from the inside.

5.2.11.3.1. LockOperationType Field

This field SHALL indicate the type of the lock operation that was performed.

5.2.11.3.2. OperationSource Field

This field SHALL indicate the source of the lock operation that was performed.

5.2.11.3.3. UserIndex Field

This field SHALL indicate the UserIndex who performed the lock operation. This SHALL be null if there is no user index that can be determined for the given operation source. This SHALL NOT be null if a user index can be determined. In particular, this SHALL NOT be null if the operation was associated with a valid credential.

5.2.11.3.4. FabricIndex Field

This field SHALL indicate the fabric index of the fabric that performed the lock operation. This SHALL be null if there is no fabric that can be determined for the given operation source. This SHALL NOT be null if the operation source is "Remote".

5.2.11.3.5. SourceNode Field

This field SHALL indicate the Node ID of the node that performed the lock operation. This SHALL be null if there is no Node associated with the given operation source. This SHALL NOT be null if the operation source is "Remote".

5.2.11.3.6. Credentials Field

This field SHALL indicate the list of credentials used in performing the lock operation. This SHALL be null if no credentials were involved.

5.2.11.4. LockOperationError Event

The door lock server sends out a LockOperationError event when a lock operation fails for various reasons.

The data of this event SHALL contain the following information:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	LockOperationType	LockOperationType-Enum	all			M
1	OperationSource	OperationSourceEnum	all			M