

Bit	Code	Feature	Conformance	Summary
2	UT	Unit	[PS]	Specifies the relevant unit and range for this dimension (mm, degrees etc.)
3	LM	Limitation	[PS]	Supports limitation of the operating range
4	SP	Speed	[PS]	Supports speed motion throttling.
5	TR	Translation	[PS].b	Drives a translation motion
6	RO	Rotation	[PS].b	Drives a rotation motion
7	MD	Modulation	[PS].b	Modulates a particular flow level (light, air, privacy ...)

5.5.5.1. Positioning Feature

This feature SHALL indicate support for position percentage over the range of 0.00% to 100.00%, with a resolution of 0.01%.

NOTE

In most of the products 0.00% = fully opened and 100.00% = fully closed but this is not always the case. For example, if the Modulation feature is supported and the ModulationType is SlatsOrientation or StripesAlignment, the panel can be fully closed at 0.00% and 100.00%, and be fully opened at 50.00%.

5.5.5.2. MotionLatching Feature

This feature SHALL indicate that the closure can be latched and unlatched. An axis with the MotionLatching feature has capabilities that will prevent actuators from moving along parts of that axis if the dimension is latched.

5.5.5.3. Unit Feature

This feature SHALL indicate additional information about the closure dimension's possible range of movement.

5.5.5.4. Limitation Feature

This feature SHALL indicate that the closure dimension supports degradation of its functioning. Reachable Position range MAY be limited compared to full scope of a nominal behavior.