

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Application	Application-Struct	desc			AP
1	Data	octstr			MS	O

6.4.7.1.1. Application Field

This field SHALL specify the Application to launch.

6.4.7.1.2. Data Field

This field SHALL specify optional app-specific data to be sent to the app.

NOTE

This format and meaning of this value is proprietary and outside the specification. It provides a transition path for device makers that use other protocols (like DIAL) which allow for proprietary data. Apps that are not yet Matter aware can be launched via Matter, while retaining the existing ability to launch with proprietary data.

6.4.7.2. StopApp Command

Upon receipt of this command, the server SHALL stop the application if it is running. The application SHALL be either

- the specified application, if the Application Platform feature is supported;
- otherwise the application corresponding to the endpoint.

The Status attribute SHALL be updated to Stopped on the Application Basic cluster of the Endpoint corresponding to the stopped application. The Status attribute SHALL be updated on any other application whose Status MAY have changed as a result of this command.

This command returns a Launcher Response.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Application	Application-Struct	desc		MS	AP

6.4.7.2.1. Application Field

This field SHALL specify the Application to stop.

6.4.7.3. HideApp Command

Upon receipt of this command, the server SHALL hide the application. The application SHALL be either