

6.6.7.8.1. ProgramIdentifier Field

This field SHALL indicate the program identifier for the program that should be cancelled from recording. This value is provided by the identifier field in [ProgramStruct](#).

6.6.7.8.2. ShouldRecordSeries Field

This field SHALL indicate whether the whole series associated to the program should be cancelled from recording. For example, invoking record program on an episode with that flag set to true, the target should schedule record the whole series.

6.6.7.8.3. ExternalIDList Field

This field, if present, SHALL indicate the list of additional external content identifiers.

6.6.7.8.4. Data Field

This field, if present, SHALL indicate app-specific data.

6.7. Content Launcher Cluster

This cluster provides an interface for launching content on a Video Player device such as a Streaming Media Player, Smart TV or Smart Screen.

This cluster would be supported on a Video Player device or devices that can playback content, such as a Streaming Media Player, Smart TV or Smart Screen. This cluster supports playing back content referenced by URL. It supports finding content by type and global identifier, and either playing the content or displaying the search results.

The cluster server for Content Launcher is implemented by an endpoint that can launch content, such as a Video Player, or an endpoint representing a Content App on such a device.

When this cluster is implemented for an Content App Endpoint (Endpoint with type “Content App” and having an Application Basic cluster), the Video Player device SHALL launch the application when a client invokes the LaunchContent or LaunchURL commands.

6.7.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision
2	Add Seasons, Episode, Any and CurrentContext to search, Added Text/Audio tracks support with PlaybackPreferences field