

6.7.5.12. TrackPreferenceStruct Type

This structure defines Text/Audio Track preferences.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Language-Code	string	max 32				M
1	Character-istics	list[CharacteristicEnum]		X	null		O
2	AudioOutputIndex	uint8		X			AT

6.7.5.12.1. LanguageCode Field

This field SHALL contain one of the standard Tags for Identifying Languages [RFC 5646](#), which identifies the primary language used in the Track.

6.7.5.12.2. Characteristics Field

This field SHALL contain a list of enumerated CharacteristicEnum values that indicate a purpose, trait or feature associated with the Track. A value of null SHALL indicate that there are no Characteristics corresponding to the Track.

6.7.5.12.3. AudioOutputIndex Field

This field if present SHALL indicate the index of the OutputInfoStruct from the OutputList attribute (from the AudioOutput cluster) and indicates which audio output the Audio Track should be played on.

This field SHALL NOT be present if the track is not an audio track.

If the track is an audio track, this field SHALL be present. A value of null SHALL indicate that the server can choose the audio output(s) to play the Audio Track on.

6.7.6. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	Accept-Header	list[string]	max 100[max 1024]	N	empty	R V	UP
0x0001	SupportedStream-ingProtocols	Supported-Protocols-Bitmap		N	0	R V	UP