

- FALSE means matches should be displayed on screen for user selection.

6.7.7.1.3. Data Field

This field, if present, SHALL indicate app-specific data.

6.7.7.1.4. PlaybackPreferences Field

This field, if present, SHALL indicate the user's preferred Text/AudioTracks and playbackPosition for the media, sent from the client to the server. If the server does not find an available track for the title being played exactly matching a Track requested here, in the list of available tracks, it may default to picking another track that closely matches the requested track. Alternately, it may go with user preferences set on the server side (it will use this option if these PlaybackPreferences are not specified). In the case of text tracks, that may mean that the subtitle text is not displayed at all. In the cases where the preferred Text/AudioTracks are not available, the server SHALL return the TextTrackNotAvailable and/or AudioTrackNotAvailable Status(es) in the LauncherResponse.

6.7.7.1.5. UseCurrentContext Field

This field, if present, SHALL indicate whether to consider the context of current ongoing activity on the receiver to fulfill the request. For example if the request only includes data in ContentSearch that specifies an Episode number, and UseCurrentContent is set to TRUE, if there is a TV series on going, the request refers to the specific episode of the ongoing season of the TV series. TRUE means current activity context MAY be considered FALSE means current activity context SHALL NOT be considered

6.7.7.2. LaunchURL Command

Upon receipt, this SHALL launch content from the specified URL.

The content types supported include those identified in the AcceptHeader and SupportedStreaming-Protocols attributes.

A check SHALL be made to ensure the URL is secure (uses HTTPS).

When playing a video stream in response to this command, an indication (ex. visual) of the identity of the origin node of the video stream SHALL be provided. This could be in the form of a friendly name label which uniquely identifies the node to the user. This friendly name label is typically assigned by the Matter Admin (ex. TV) at the time of commissioning and, when it's a device, is often editable by the user. It might be a combination of a company name and friendly name, for example, "Acme" or "Acme Streaming Service on Alice's Phone".

This command returns a Launch Response.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ContentURL	string	any			M
1	DisplayString	string	any		MS	O