

index in the Input List.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Index	uint8	all			M

6.9.7.1.1. Index Field

This field SHALL indicate the index field of the [InputInfoStruct](#) from the InputList attribute in which to change to.

6.9.7.2. ShowInputStatus Command

Upon receipt, this command SHALL display the active status of the input list on screen.

6.9.7.3. HideInputStatus Command

Upon receipt, this command SHALL hide the input list from the screen.

6.9.7.4. RenameInput Command

Upon receipt, this command SHALL rename the input at a specific index in the Input List.

Updates to the input name SHALL appear in the device's settings menus.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Index	uint8	all			M
1	Name	string	all			M

6.10. Media Playback Cluster

This cluster provides an interface for controlling Media Playback (PLAY, PAUSE, etc) on a media device such as a TV, Set-top Box, or Smart Speaker.

This cluster server would be supported on Video Player devices or endpoints that provide media playback, such as a Content App. This cluster provides an interface for controlling Media Playback.

6.10.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision
2	Added Text/Audio tracks support, Audio-while-advancing (AA) feature, StateChanged event