

6.10.7.13.2. AudioOutputIndex Field

This value is the index field of the OutputInfoStruct from the OutputList attribute (from the AudioOutput cluster) and indicates which audio output the Audio Track should be played on. This field is absent for Text Tracks and only present for Audio Tracks. A value of null SHALL indicate that the server can choose the audio output(s) to play the Audio Track on.

6.10.7.14. ActivateTextTrack Command

This command is used to activate a specific Text Track for the media being played.

Upon receipt, the server SHALL set the active Text Track to the one identified by the TrackID in the Track catalog for the streaming media. If the TrackID does not exist in the Track catalog, OR does not correspond to the streaming media OR no media is being streamed at the time of receipt of this command, the server SHALL return an error status of INVALID_ARGUMENT.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	TrackID	string	max 32			M

6.10.7.14.1. TrackID Field

This field SHALL indicate the Text Track to activate.

6.10.7.15. DeactivateTextTrack Command

This command is used to deactivate a specific Text Track for the media being played.

If a Text Track is active (i.e. being displayed), upon receipt of this command, the server SHALL stop displaying it.

6.10.8. Events

ID	Name	Priority	Access	Conformance
0x00	StateChanged	INFO	V	O

6.10.8.1. StateChanged Event

If supported, this event SHALL be generated when there is a change in any of the supported attributes of the Media Playback cluster. This event SHALL have the following data fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0x0000	CurrentState	PlaybackStateEnum	desc			M
0x0001	StartTime	epoch-us	desc			AS
0x0002	Duration	uint64	desc			AS