

6.13.5.4.1. CatalogVendorID Field

This field SHALL indicate the Connectivity Standards Alliance-issued vendor ID for the catalog. The DIAL registry SHALL use value 0x0000.

Content App Platform providers will have their own catalog vendor ID (set to their own Vendor ID) and will assign an ApplicationID to each Content App.

6.13.5.4.2. ApplicationID field

This field SHALL indicate the application identifier, expressed as a string, such as "PruneVideo" or "Company X". This field SHALL be unique within a catalog.

6.13.5.5. TimeWindowStruct Type

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	TimeWindowIndex	uint16	all	X			M
1	DayOfWeek	Day-OfWeek-Bitmap	desc				M
2	TimePeriod	list[TimePeriodStruct]	desc				M

6.13.5.5.1. TimeWindowIndex Field

This field SHALL indicate a unique index of a specific time window. This value may be used to indicate a selected time window which will be removed from the BlockContentTimeWindow attribute.

6.13.5.5.2. DayOfWeek Field

This field SHALL indicate a day of week.

6.13.5.5.3. TimePeriod Field

This field SHALL indicate one or more discrete time periods.

6.13.5.6. TimePeriodStruct type

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	StartHour	uint8	0 to 23				M
1	StartMinute	uint8	0 to 59				M
2	EndHour	uint8	0 to 23				M