

6.13.7.10. BlockApplicationList Attribute

This attribute SHALL indicate a set of applications that SHALL be blocked when the Content Control feature is activated.

6.13.7.11. BlockContentTimeWindow Attribute

This attribute SHALL indicate a set of periods during which the playback of content on media device SHALL be blocked when the Content Control feature is activated. The media device SHALL reject any request to play content during one period of this attribute. If it is entering any one period of this attribute, the media device SHALL block content which is playing and generate an event EnteringBlockContentTimeWindow. There SHALL NOT be multiple entries in this attribute list for the same day of week.

6.13.8. Commands

ID	Name	Direction	Response	Access	Conformance
0x00	UpdatePIN	client ⇒ server	Y	M T	PM
0x01	ResetPIN	client ⇒ server	ResetPINRe- sponse	A T	PM
0x02	ResetPINRe- sponse	client ⇐ server	N		PM
0x03	Enable	client ⇒ server	Y	M T	M
0x04	Disable	client ⇒ server	Y	M T	M
0x05	AddBonus- Time	client ⇒ server	Y	O	ST
0x06	SetScreenDai- lyTime	client ⇒ server	Y	M	ST
0x07	BlockUnrated- Content	client ⇒ server	Y	M	BU
0x08	UnblockUnrat- edContent	client ⇒ server	Y	M	BU
0x09	SetOnDeman- dRatingTh- reshold	client ⇒ server	Y	M	OCR
0x0A	SetScheduled- ContentRat- ingThreshold	client ⇒ server	Y	M	SCR
0x0B	AddBlockCha- nnels	client ⇒ server	Y	M	BC
0x0C	Remove- BlockChan- nels	client ⇒ server	Y	M	BC