

state SHALL remain unchanged. See [Operational State Cluster](#) for details on the operational states.

If this command is received and any fields sent with the command do not meet the constraints of any of the associated attributes (i.e. bearing the same name as the field or as described in the field description), the server SHALL respond with a response of CONSTRAINT_ERROR and the attributes and state SHALL remain unchanged.

If the StartAfterSetting field is present in the command but the Start command of the Operational State cluster or one of its derivatives on the same endpoint as this cluster is not supported, the server SHALL respond with a response of INVALID_COMMAND and the attributes and state SHALL remain unchanged.

Otherwise:

- The attributes associated with any included fields SHALL be set to the values of those fields.
- The attributes associated with any missing fields SHALL be set to the values as specified in descriptions of the missing fields.
- If the StartAfterSetting field is included:
 - If the value of StartAfterSetting is TRUE, oven operation SHALL start.
 - If the value of StartAfterSetting is FALSE, oven operation SHALL NOT start.

8.13.6.3. AddMoreTime Command

This command is used to add more time to the CookTime attribute of the server.

This command supports these fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	TimeToAdd	elapsed-s	1 to Max-CookTime			M

8.13.6.3.1. TimeToAdd Field

This field SHALL indicate the number of seconds to be added to the CookTime attribute.

8.13.6.3.2. Effect on Receipt

Upon receipt of this command, if the sum of the value of the TimeToAdd field and the current value of the CookTime attribute is greater than the MaxCookTime attribute, the server SHALL respond with a response of CONSTRAINT_ERROR and the command SHALL be ignored.

If this command is received while the operational state of the server cannot support the command in that state, the server SHALL respond with an INVALID_IN_STATE response. See [Operational State Cluster](#) for details on the operational states.

Otherwise, the server SHALL add the value of the TimeToAdd field to the value of the CookTime attribute of this cluster and the server SHALL add the value of the TimeToAdd field to the value of