

continue to run the same program and meet the same user settings (e.g. ECO mode), but may take more or less time to complete the cycle. The new reported Forecast will start from the current time, i.e. the slots that have already been completed SHALL NOT be included in the new forecast.

The command status returned SHALL be SUCCESS, otherwise if the Cause is not permitted, or the constraints field value does not meet the defined constraints, the command SHALL be rejected with CONSTRAINT_ERROR, otherwise the command SHALL be rejected with FAILURE.

9.2.9.8. CancelRequest Command

Allows a client to request cancellation of a previous adjustment request in a [StartTimeAdjustRequest](#), [ModifyForecastRequest](#) or [RequestConstraintBasedForecast](#) command.

9.2.9.8.1. Effect on receipt

On receipt of this command, the ESA SHALL attempt to cancel the effects of any previous adjustment request commands, and re-evaluate its forecast for intended operation ignoring those previous requests.

If the ESA [ForecastUpdateReason](#) was already **Internal Optimization**, then the command SHALL be rejected with INVALID_IN_STATE.

If the command is accepted, the ESA SHALL update its [ESAState](#) if required, and the command status returned SHALL be SUCCESS. The ESA SHALL update its [Forecast](#) attribute to match its new intended operation, and update the [ForecastUpdateReason](#) to **Internal Optimization**.

9.2.10. Events

ID	Name	Priority	Quality	Access	Conformance
0x00	PowerAdjust-Start	INFO		V	PA
0x01	PowerAdjust-End	INFO		V	PA
0x02	Paused	INFO		V	PAU
0x03	Resumed	INFO		V	PAU

9.2.10.1. PowerAdjustStart Event

This event SHALL be generated when the Power Adjustment session is started.

9.2.10.2. PowerAdjustEnd Event

This event SHALL be generated when the Power Adjustment session ends.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Cause	CauseEnum	all			M