

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	WIFINM

10.2.3. Cluster ID

ID	Name
0x0451	Wi-Fi Network Management

10.2.4. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	SSID	octstr	1 to 32	N X		R V	M
0x0001	PassphraseSurrogate	uint64	all	N X		R M	M

10.2.4.1. SSID Attribute

This attribute SHALL indicate the SSID of the primary Wi-Fi network provided by this device.

A value of null SHALL indicate that no primary Wi-Fi network is available (e.g. because the Wi-Fi network has not yet been configured by the user).

NOTE

The SSID in Wi-Fi is a collection of 1-32 bytes, the text encoding of which is not specified. Implementations must be careful to support transferring these byte strings without requiring a particular encoding. The most common encoding is UTF-8, however this is just a convention. Some configurations may use Latin-1 or other character sets.

10.2.4.2. PassphraseSurrogate Attribute

This attribute SHALL contain an arbitrary numeric value; this value SHALL increase whenever the passphrase or PSK associated with the primary Wi-Fi network provided by this device changes.

A value of null SHALL indicate that no primary Wi-Fi network is available.

Clients can subscribe to this attribute or compare its value to a locally cached copy to detect if a cached passphrase value has become stale.

It is RECOMMENDED that servers implement this attribute as either a timestamp or a counter. When implemented as a counter it SHOULD be initialized with a random value.

NOTE

The passphrase itself is not exposed as an attribute to avoid its unintentional retrieval or caching by clients that use wildcard reads or otherwise routinely read all available attributes. It can be retrieved using the [NetworkPassphraseRequest](#)