

10.3.5. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	Border-Router-Name	string	1 to 63			R V	M
0x0001	BorderAgentID	octstr	16			R V	M
0x0002	Thread-Version	uint16	all	F		R V	M
0x0003	InterfaceEnabled	bool	all	N		R V	M
0x0004	Active-Dataset-Time-stamp	uint64	all	N X		R V	M
0x0005	Pending-Dataset-Time-stamp	uint64	all	N X		R V	M

10.3.5.1. BorderRouterName Attribute

This attribute SHALL indicate a user-friendly name identifying the device model or product of the Border Router in MeshCOP (DNS-SD service name) as defined in the [Thread specification](#), and has the following recommended format: `<VendorName> <ProductName>._meshcop._udp`. An example name would be `ACME Border Router (74be)._meshcop._udp`.

10.3.5.2. BorderAgentID Attribute

This attribute SHALL indicate a 16-byte globally unique ID for a Thread Border Router device. This ID is manufacturer-specific, and it is created and managed by the border router's implementation.

10.3.5.3. ThreadVersion Attribute

This attribute SHALL indicate the Thread version supported by the Thread interface configured by the cluster instance.

The format SHALL match the value mapping defined in the "Version TLV" section of the [Thread specification](#). For example, Thread 1.3.0 would have ThreadVersion set to 4.

10.3.5.4. InterfaceEnabled Attribute

This attribute SHALL indicate whether the associated IEEE 802.15.4 Thread interface is enabled or disabled.