

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Pending-Dataset	octstr	max 254			M

This PendingDataset field SHALL contain the pending dataset to which the Thread network should be updated. The format of the data SHALL be an octet string containing the raw Thread TLV value of the pending dataset, as defined in the [Thread specification](#).

If any of the parameters in the PendingDataset is invalid, the command SHALL fail with a status of INVALID_COMMAND.

Otherwise, this command SHALL configure the pending dataset of the Thread network to which the Border Router is connected, with the value given in the PendingDataset parameter. The Border Router will manage activation of the pending dataset as defined in the [Thread specification](#).

10.4. Thread Network Directory Cluster

This cluster stores a list of Thread networks (including the credentials required to access each network), as well as a designation of the user's preferred network, to facilitate the sharing of Thread networks across fabrics.

10.4.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision

10.4.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	THNETDIR

10.4.3. Cluster ID

ID	Name
0x0453	Thread Network Directory

10.4.4. Data Types

10.4.4.1. ThreadNetworkStruct Type

Represents the data associated with a Thread Network.