

encoder dedicated to a specific stream, allowing for simultaneous recording and live viewing at the highest possible quality.

11.2.1.2.2. Multiple Stream Resource Conflict Resolution

The camera **SHOULD** utilize the highest resolution and bitrate the network can support for the stream that is at the top of the video stream priority list. For multiple simultaneous liveview clients, the camera **MAY** automatically adjust the resolution and bitrate while still maintaining a good quality of experience for all viewers.

If the accommodation of a new stream request requires an adjustment of video parameters (resolution, bitrate, etc) for an existing stream, it **SHALL** abide by the minimum configuration requirements of the existing stream. Otherwise, the new stream request **SHALL** be rejected with a **FAILED** notification to the requester.

11.2.2. Revision History

The global ClusterRevision attribute value **SHALL** be the highest revision number in the table below.

Rev	Description
1	Initial release

11.2.3. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	AVSM

11.2.4. Cluster ID

ID	Name
0x0551	Camera AV Stream Management

11.2.5. Features

This cluster **SHALL** support the FeatureMap bitmap attribute as defined below.

Table 19. Camera AV Stream Management Features

Bit	Code	Feature	Conformance	Description
0	ADO	Audio	O.a+	Audio Streams supported
1	VDO	Video	O.a+	Video Streams supported
2	SNP	Snapshot	O.a+	Snapshot Streams supported