

11.2.7.15. SupportedStreamUsages Attribute

This attribute SHALL indicate the list of [Stream Usages](#) that are supported by the camera. Manufacturers SHALL provide a usages list that is appropriate to their product. If a usage is found in this list, then it can be used in the [StreamUsagePriorities](#) attribute. The ordering and values of this list SHALL match the values found in [StreamUsagePriorities](#) after a factory reset.

11.2.7.16. AllocatedVideoStreams Attribute

This attribute SHALL indicate the list of allocated video streams on the device.

11.2.7.17. AllocatedAudioStreams Attribute

This attribute SHALL indicate the list of allocated audio streams on the device.

11.2.7.18. AllocatedSnapshotStreams Attribute

This attribute SHALL indicate the list of allocated snapshot streams on the device.

11.2.7.19. StreamUsagePriorities Attribute

This attribute SHALL indicate a list of the [video stream usages](#) represented in a ranked order of their priorities, starting with Index 0 having the stream usage type with the highest priority. See [Resource Management and Stream Priorities](#) for further details. Only usages found in the [SupportedStreamUsages](#) attribute can be included. To change the contents, use the [SetStreamPriorities](#) command. Manufacturers SHALL provide a default ranked priorities list that is appropriate to their product and this default ranking SHALL exactly match the contents of [SupportedStreamUsages](#). Clients can use the contents of the [SupportedStreamUsages](#) to restore this default state if the contents have been changed by the [SetStreamPriorities](#) command.

11.2.7.20. SoftRecordingPrivacyModeEnabled Attribute

This attribute indicates the current value of the soft privacy mode for transports using the [Stream Usage](#) types [Recording](#) and [Analysis](#). A value of TRUE indicates that delivery of video frames and audio samples from any streams to these transports is skipped. A value of TRUE also indicates that no new transports using these stream usage values can be created or started. When FALSE, these transports can be resumed or started, and have video frames and audio samples delivered.

When this attribute is set to TRUE, any active [WebRTC transports](#) using these stream usage types SHALL terminate the session by calling [End](#) using [WebRTCEndReasonEnum](#) PrivacyMode.

11.2.7.21. SoftLivestreamPrivacyModeEnabled Attribute

This attribute indicates the current value of the soft privacy mode for transports using the [Stream Usage](#) type [LiveView](#). A value of TRUE indicates that delivery of video frames and audio samples from any streams to these transports is skipped. A value of TRUE also indicates that no new transports using this stream usage type can be created or started. When FALSE, these transports can be resumed or started, and have video frames and audio samples delivered.

When this attribute is set to TRUE, any active [WebRTC transports](#) using this stream usage type SHALL terminate the session by calling [End](#) using [WebRTCEndReasonEnum](#) PrivacyMode.