

- Append the new [VideoStreamStruct](#) to the [AllocatedVideoStreams](#).
- If [DigitalPTZ](#) is supported in [Camera AV Settings User Level Management](#):
 - Add a new [DPTZStruct](#) entry in [DPTZStreams](#) using the new VideoStreamID and current value of [Viewport](#).
- Return the newly allocated VideoStreamID in [VideoStreamAllocateResponse](#).

11.2.8.5. VideoStreamAllocateResponse Command

This command SHALL be sent by the camera in response to the VideoStreamAllocate command, carrying the newly allocated or re-used video stream identifier.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	VideoStreamID	VideoStreamIDType	all			M

11.2.8.5.1. VideoStreamID Field

This field SHALL be a [VideoStreamIDType](#) representing the newly created unique video stream identifier.

11.2.8.6. VideoStreamModify Command

This command SHALL be used to modify a stream specified by the VideoStreamID.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	VideoStreamID	VideoStreamIDType	all			M
1	WatermarkEnabled	bool	all			[WMARK].d+
2	OSDEnabled	bool	all			[OSD].d+

11.2.8.6.1. VideoStreamID Field

This field SHALL be a [VideoStreamIDType](#) representing the video stream to modify.

11.2.8.6.2. WatermarkEnabled Field

This field SHALL indicate whether a watermark can be applied on the video stream. A value of TRUE means that watermarking has been requested for that stream. If this field is not present, then no change to the existing value SHALL be made.

11.2.8.6.3. OSDEnabled Field

This field SHALL indicate whether the OSD (On-Screen Display) can be applied on the video stream.