

11.3.7.7.4. ZoomDelta Field

This field SHALL represent a percentage change to the size of the [Viewport](#) is within the Sensor-Width and SensorHeight found in [VideoSensorParams](#). A value of 0 means no change. A negative value means make the viewport larger. A positive value means make the viewport smaller.

11.3.7.7.5. Effect on Receipt

The process below SHALL be followed by the camera when receiving this command:

- If a VideoStreamID entry does not exist in [DPTZStreams](#):
 - Fail the command with the status code NOT_FOUND, and end processing with no other side-effects.
- If DeltaX is present and not 0:
 - Add DeltaX to the X1 and X2 fields of the VideoStreamID viewport bounding rectangle.
- If DeltaY is present and not 0:
 - Add DeltaY to the Y1 and Y2 fields of the VideoStreamID viewport bounding rectangle.
- If ZoomDelta is present and not 0:
 - Scale the VideoStreamID viewport bounding rectangle by the percentage value; anchoring the re-scaled rectangle at the center point of the existing viewport.
- If the aspect ratio following application of the delta values does not match the aspect ratio of the video stream:
 - Clip the viewport to the aspect ratio of the video stream while maintaining the upper left location.
- If the resultant requested viewport is smaller than the [MinViewportResolution](#)
 - Use size in [MinViewportResolution](#) while preserving the upper left location if possible.
- If the requested viewport is larger than [SensorWidth](#) or [SensorHeight](#) in the [VideoSensorParams](#):
 - Use the sensor size values.
- If any portion of requested viewport falls outside the sensor Cartesian plane:
 - Change the upper left of the requested viewport to the nearest point allowing the viewport to be within the sensor Cartesian plane.
- Apply the new viewport values to the video stream with ID VideoStreamID.
- Update the entry in [DPTZStreams](#) with the new viewport values.
- Respond with the status code SUCCESS

11.4. WebRTC Transport

11.4.1. Background Info

WebRTC (Web Real-Time Communication) is a real-time communication transport technology built on a set of standards that allows audio and video communication between two peers and also supports the transport of arbitrary data between them using an Offer/Answer model.