

them. In the example flows shown below the Camera is the Provider.

11.4.2.2. Requestor

The Requestor role is expressed by implementing the [WebRTC Transport Requestor Cluster](#) and is implemented by devices which want to watch or listen to the streams produced by a Provider. Requestors only initiate outbound sessions. In the example flows shown below the Controller is the Requestor.

11.4.3. Signaling Flows

The following sequence diagrams show the back and forth commands, statuses, and command responses that are involved in the WebRTC session lifecycle.

11.4.3.1. Normal Flow

In this flow, the controller starts the signaling sequence by providing an SDP Offer to the camera via [ProvideOffer](#). If the camera is successful in starting a session, it SHALL send a [ProvideOfferResponse](#) with the allocated WebRTC session ID, the allocated video stream ID, and the allocated audio stream ID. Otherwise, it SHALL respond with a StatusReport with a FAILURE status code. Subsequently, the camera SHALL follow up with an SDP Answer. The second phase is the trickle ICE candidate exchange, where both peers determine their ICE candidates and exchange them via [ProvideICECandidates](#) and [ICECandidates](#). In the third phase, the actual connection is established and the WebRTC session becomes active.

Lastly, when the controller needs to end the session, it SHALL send the [EndSession](#) command to the camera. If the camera needs to end the session, it SHALL send the [End](#) command to the controller.

