

11.5. WebRTC Transport Provider Cluster

The WebRTC transport provider cluster provides a way for stream providers (e.g. Cameras) to stream or receive their data through WebRTC. Devices implementing this cluster SHALL also implement [Camera AV Stream Management Cluster](#) on the same endpoint.

11.5.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial version of the WebRTC Transport Provider Cluster

11.5.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	WEBRTCP

11.5.3. Cluster ID

ID	Name
0x0553	WebRTC Transport Provider

11.5.4. Features

This cluster SHALL support the FeatureMap bitmap attribute as defined below.

Bit	Code	Feature	Conformance	Summary
0	METADATA	Metadata	P, O	Supports metadata transmission in WebRTC sessions

11.5.4.1. Metadata Feature

When this feature is supported and a session activates it, a WebRTC DataChannel using the protocol name `urn:csa:matter:av-metadata` SHALL be used for transmitting the metadata. The ability to include metadata is supported on a per session basis.

This feature is designed to be [JSEP](#) compliant with the [RTCDDataChannel](#) [<https://www.w3.org/TR/webrtc/#rtcdatachannel>] object interface and consists of [AVMetadataStruct](#) content.

If [SFrame End-to-End Encryption](#) is active in a session, all metadata transmissions SHALL be sent using the protocol name `urn:csa:matter:sframe:av-metadata` instead with each transmission being wrapped in SFrames.