

ID	Name	Type	Constraint	Quality	Fallback	Conformance
5	AudioStreamID	AudioStreamIDType	all	X		O,c+
6	ICEServers	list[ICE-Server-Struct]	max 10			O
7	ICETransportPolicy	string	max 16			O
8	Meta-dataEnabled	bool	all			METADATA
9	SFrameConfig	SFrameStruct	all			P, O

11.5.7.3.1. WebRTCSessionID Field

This field SHALL be a [WebRTCSessionID](#) and contain the ID of an established WebRTC session or null if requesting a new session.

11.5.7.3.2. SDP Field

This field SHALL contain the string based [SDP Offer](#). See [WebRTC Transport](#) for further details on SDP and Offer/Answer semantics.

11.5.7.3.3. StreamUsage Field

This field SHALL contain the [StreamUsageEnum](#) that indicates the stream usage for this session.

11.5.7.3.4. OriginatingEndpointID Field

This field SHALL indicate the endpoint that originates this command. This endpoint SHALL be used when acting as a client to invoke the commands on the Requestor cluster.

11.5.7.3.5. VideoStreamID Field

This field SHALL have the following semantics:

- If not present, video is not being requested.
- If present and null, automatic assignment of a video stream is requested.
- If present and not null, the specific stream identified by the [VideoStreamIDType](#) is requested.

In a reOffer flow, this field SHALL be set to the existing VideoStreamID stored for this session.

11.5.7.3.6. AudioStreamID Field

This field SHALL have the following semantics: