

11.5.7.4.2. VideoStreamID Field

This field SHALL contain the [VideoStreamIDType](#) used for this session. If no video stream was used, null SHALL be passed.

11.5.7.4.3. AudioStreamID Field

This field SHALL contain the [AudioStreamIDType](#) used for this session. If no audio stream was used, null SHALL be passed.

11.5.7.5. ProvideAnswer Command

This command SHALL be initiated from a Node in response to an Offer that was previously received from a remote peer. It SHALL have the following data fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	WebRTCSessionID	WebRTCSessionID	all			M
1	SDP	string	all			M

This command SHALL respond with a response status of NOT_FOUND if the WebRTCSessionID does not match an entry in [CurrentSessions](#), or if the matching entry's associated fabric and PeerNodeID do not match the accessing fabric and the Peer Node ID entry stored in the Secure Session Context of the session this command was received on.

11.5.7.5.1. WebRTCSessionID Field

This field SHALL contain the [WebRTCSessionID](#) of the established WebRTC session.

11.5.7.5.2. SDP Field

This field SHALL contain the string based [SDP](#) Answer. See [WebRTC Transport](#) for further details on SDP and Offer/Answer semantics.

11.5.7.6. ProvideICECandidates Command

This command allows for string based [ICE candidates](#) [<https://rfc-editor.org/rfc/rfc8839#section-5.1>] generated after the initial Offer / Answer exchange, via a JSEP [onicecandidate](#) [<https://datatracker.ietf.org/doc/html/rfc9429#section-4.1.20>] event, a DOM [rtcpeerconnectioniceevent](#) [<https://www.w3.org/TR/webrtc/#dom-rtcpeerconnectioniceevent>] event, or other WebRTC compliant implementations, to be added to a session during the gathering phase. This is typically used for STUN or TURN discovered candidates, or to indicate the end of gathering state.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	WebRTCSessionID	WebRTCSessionID	all			M