

11.6.5. Commands

ID	Name	Direction	Response	Access	Quality	Conformance
0x00	Offer	client ⇒ server	Y	O	L	M
0x01	Answer	client ⇒ server	Y	O	L	M
0x02	ICECandidates	client ⇒ server	Y	O	L	M
0x03	End	client ⇒ server	Y	O	L	M

11.6.5.1. Offer Command

This command provides the stream requestor with WebRTC session details. It is sent following the receipt of a [SolicitOffer](#) command or a re-Offer initiated by the Provider.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	WebRTCSessionID	WebRTCSessionID	all			M
1	SDP	string	all			M
2	ICEServers	list[ICE-Server-Struct]	max 10			O
3	ICETransportPolicy	string	max 16			O

This command SHALL respond with a response status of NOT_FOUND if the WebRTCSessionID does not match an entry in [CurrentSessions](#), or if the matching entry's associated fabric and [PeerNodeID](#) do not match the accessing fabric and the Peer Node ID entry stored in the Secure Session Context (see Chapter 4 Secure Channel, Secure Session Context section, in [\[MatterCore\]](#)) of the session this command was received on.

11.6.5.1.1. WebRTCSessionID Field

This field SHALL contain the ID of the established WebRTC session.

11.6.5.1.2. SDP Field

This field SHALL contain the string based [SDP Offer](#). See [WebRTC Transport](#) for further details on SDP and Offer/Answer semantics.