

11.6.5.1.3. ICEServers Field

This field SHALL be a list of [ICEServerStruct](#) which contains the ICE servers and their credentials to use for this session. See [ICEServerStruct](#) for further details.

11.6.5.1.4. ICETransportPolicy Field

This field controls the gathering and usage of ICE candidates and SHALL have one of the values found in [ICETransportPolicy](#).

11.6.5.2. Answer Command

This command provides the stream requestor with the WebRTC session details (i.e. Session ID and SDP answer), It is the next command in the Offer/Answer flow to the [ProvideOffer](#) command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	WebRTCSessionID	WebRTCSessionID	all			M
1	SDP	string	all			M

This command SHALL respond with a response status of NOT_FOUND if the WebRTCSessionID does not match an entry in [CurrentSessions](#), or if the matching entry's associated fabric and [PeerNodeID](#) do not match the accessing fabric and the Peer Node ID entry stored in the Secure Session Context of the session this command was received on.

11.6.5.2.1. WebRTCSessionID Field

This field SHALL contain the [WebRTCSessionID](#) of the established WebRTC session.

11.6.5.2.2. SDP Field

This field SHALL contain the string based [SDP](#) Answer. See [WebRTC Transport](#) for further details on SDP and Offer/Answer semantics.

11.6.5.3. ICECandidates Command

This command allows for the object based [ICE candidates](#) [<https://rfc-editor.org/rfc/rfc8839#section-5.1>] generated after the initial Offer / Answer exchange, via a JSEP [onicecandidate](#) [<https://data-tracker.ietf.org/doc/html/rfc9429#section-4.1.20>] event, a DOM [rtcpeerconnectioniceevent](#) [<https://www.w3.org/TR/webrtc/#dom-rtcpeerconnectioniceevent>] event, or other WebRTC compliant implementations, to be added to a session during the gathering phase. This is typically used for STUN or TURN discovered candidates, or to indicate the end of gathering state.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	WebRTCSessionID	WebRTCSessionID	all			M