

ID	Name	Type	Constraint	Quality	Fallback	Conformance
1	ICECandidates	list[ICECandidateStruct]	min 1			M

This command SHALL respond with a response status of NOT_FOUND if the WebRTCSessionID does not match an entry in [CurrentSessions](#), or if the matching entry's associated fabric and [PeerNodeID](#) do not match the accessing fabric and the Peer Node ID entry stored in the Secure Session Context of the session this command was received on.

11.6.5.3.1. WebRTCSessionID Field

This field SHALL contain the [WebRTCSessionID](#) of the established WebRTC session.

11.6.5.3.2. ICECandidates Field

This field SHALL contain a list of [JSEP](#) compliant [ICE Candidate Format](#) [<https://datatracker.ietf.org/doc/html/rfc9429#section-3.5.2.1>] objects.

11.6.5.4. End Command

This command notifies the stream requestor that the provider has ended the WebRTC session.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	WebRTCSessionID	WebRTCSessionID	all			M
1	Reason	WebRTCEndReasonEnum	all			M

11.6.5.4.1. WebRTCSessionID Field

This field SHALL contain the [WebRTCSessionID](#) of the established WebRTC session.

11.6.5.4.2. Reason Field

This field SHALL be one of the values in [WebRTCEndReasonEnum](#).

11.6.5.4.3. Effect on Receipt

The process below SHALL be followed by the server when receiving this command:

- If WebRTCSessionID does not match a value in [CurrentSessions](#):
 - Respond with a response status of NOT_FOUND
- If the accessing Peer Node ID stored in the Secure Session Context and the accessing fabric do not match the [PeerNodeID](#) and associated fabric for the WebRTCSessionID entry in [CurrentSessions](#):