

Value	Name	Summary	Conformance
0	Command	Triggered only via a command invocation	M
1	Motion	Triggered via motion detection or command	M
2	Continuous	Triggered always when transport status is Active	M

11.7.6.1.1. Command Value

When set to this value, transport will only occur if [ManuallyTriggerTransport](#) is invoked.

11.7.6.1.2. Motion Value

When set to this value, transport will occur if either the Motion Detector becomes triggered, or [ManuallyTriggerTransport](#) is invoked. This is generally known as event driven recording.

11.7.6.1.3. Continuous Value

When set to this value, transport will always occur so long as the [TransportStatus](#) is Active. This is generally known as 24/7 always-on recording.

11.7.6.2. TransportStatusEnum Type

This data type is derived from enum8.

Value	Name	Summary	Conformance
0	Active	Push Transport can transport AV Streams	M
1	Inactive	Push Transport cannot transport AV Streams	M

11.7.6.3. ContainerFormatEnum Type

This data type is derived from enum8.

Value	Name	Summary	Conformance
0	CMAF	CMAF container format	M

11.7.6.3.1. CMAF Value

CMAF (Common Media Application Format) is a container format based on the [ISO Base Media File Format](#) and is described in [MPEGCMAF](#). Nodes using CMAF as the container format SHALL also use CMAFIngest as the ingestion format.