

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
6	CENCKeyID	octstr	16				P, CENCKey
7	Meta-dataEnabled	bool	all				[META-DATA]

11.7.6.8.1. CMAFInterface Field

This field SHALL indicate the selected Interface of the CMAF container. The Interface chosen determines the number and type of operations that occur within each CMAF session. See [CMAFInterfaceEnum](#) for details on CMAF Interfaces.

11.7.6.8.2. SegmentDuration Field

This field SHALL indicate the segment duration (in milliseconds) of the CMAF container. This value SHALL be a multiple of the [KeyFrameInterval](#) for the associated video stream. It is RECOMMENDED to use a value of 4000 (4 seconds).

11.7.6.8.3. ChunkDuration Field

This field SHALL indicate the chunk duration (in milliseconds) of the CMAF container. A value of 0 SHALL indicate that chunks are not used.

When chunking is used, an even divisor of SegmentDuration SHOULD be used that aligns with the video frame rate and audio frame duration. RECOMMENDED values are 1/2, 1/4, or 1/8 of the SegmentDuration depending on the end to end latency requirements needed. Each chunk results in an additional 144 bytes of overhead in the resulting file.

11.7.6.8.4. SessionGroup Field

This field SHALL identify the grouping semantic of the CMAF [Session](#) numbering between various CMAF transports on the same Fabric. See [Session Grouping](#) for more details.

11.7.6.8.5. TrackName Field

This field SHALL identify the CMAF [Track](#) name value used inside the CMAF computed extended path fields portion of the CMAF POST_URL. See [Track Naming](#) for full details.

11.7.6.8.6. CENCKey Field

This field, if present, SHALL indicate the [CENC](#) key to be used to encrypt the CMAF data. When absent, the CMAF data SHALL be sent without CENC encryption added. See [CMAF Background](#) for further details on CMAF CENC encryption.

11.7.6.8.7. CENCKeyID Field

This field, if present, SHALL indicate the opaque [CENC](#) Key ID (KID) that represents the key in the Controllers ecosystem. This field maps to the KID value as specified in ISO 23001-7:2023 or later.