

See [CMAF Background](#) for further details on CMAF CENC encryption.

11.7.6.8.8. MetadataEnabled Field

This field, if present and true, indicates that [AVMetadataStruct](#) based Metadata tracks and boxes MAY be included in the CMAF segments. If this field is not present or is false, metadata tracks and boxes SHALL NOT be included.

Metadata within CMAF segments when used, SHALL be encoded as follows:

- Use **urim** as the codec-type.
- Use **meta** as the content-type.
- Use **urn:csa:matter:av-metadata** as the uri.

Placement of the metadata SHALL be as follows:

- Use a single Track for time-synced data points as described in [CMAF-Ingest Interface-1 Section 6.6 Requirements for Timed Metadata Tracks](#) [<https://dashif.org/Ingest/#interface-1-timed-metadata>].
- Use a single Box for non-time synced data points.

11.7.6.9. ContainerOptionsStruct Type

This struct encodes the specific container type options struct

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Container-Type	Container-FormatEnum	all				M
1	CMAFContainerOptions	CMAFContainerOptionsStruct					Container-Type == CMAF

11.7.6.9.1. ContainerType Field

This field SHALL indicate the container type chosen for this transport.

11.7.6.9.2. CMAFContainerOptions Field

This field SHALL contain a [CMAF Container Options](#) if the ContainerType is set to CMAF, otherwise this field SHALL be omitted.

11.7.6.10. TransportZoneOptionsStruct Type

This struct encodes the options that configure the per [Zone](#) portion of a Trigger configuration.