

11.7.6.13.7. IngestMethod Field

This field SHALL be of type [IngestMethodsEnum](#) and represents the Ingest Method to be used.

11.7.6.13.8. ContainerOptions Field

This field SHALL be of type [ContainerOptionsStruct](#) and represents the type of Push AV Stream Container to be uploaded and any additional options relating to the Container Format used.

11.7.6.13.9. ExpiryTime Field

This field SHALL be an unsigned 32 bit integer representing the TTL in seconds of a transport allocation. If not present, the transport SHALL never expire.

11.7.6.14. TransportConfigurationStruct Type

This encodes the current configuration of an allocated transport.

Access Modifier: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	ConnectionID	PushTransportConnectionID	0 to 65534				M
1	TransportStatus	TransportStatusEnum	all				M
2	TransportOptions	TransportOptionsStruct					O

11.7.6.14.1. ConnectionID Field

This field SHALL be a [PushTransportConnectionID](#) representing a unique transport.

11.7.6.14.2. TransportStatus Field

This field SHALL represent the [Stream Transport Status](#) of the transport.

11.7.6.14.3. TransportOptions Field

This field SHALL represent the [Stream Transport Options](#) of the transport.

11.7.6.15. PushTransportConnectionID Type

This data type is derived from uint16.

It represents an allocated transport. This value starts at 0 and monotonically increases by 1 with each new allocation provisioned by the Node. A value incremented past 65534 SHALL wrap to 0. The Node SHALL verify that the incremented ID does not match any other ID. If such a match is