

- Save the resulting [AudioStreamID](#) into the *TransportOptions*.
- If the [VideoStreamID](#) field of the passed in *TransportOptions* is present, and an entry for it is not found in the [AllocatedVideoStreams](#) list:
 - Fail the command with the cluster-specific status code of `InvalidStream`, and end processing with no other side effects.
- If the [AudioStreamID](#) field of the passed in *TransportOptions* is present, and an entry for it is not found in the [AllocatedAudioStreams](#) list:
 - Fail the command with the cluster-specific status code of `InvalidStream`, and end processing with no other side effects.
- If the ContainerOptions [ContainerType](#) is `CMAF`:
 - If the requested [SegmentDuration](#) is not a multiple of [KeyFrameInterval](#):
 - Fail the command with the cluster-specific status code of `InvalidOptions`, and end processing with no other side effects.
- Create a new [PushTransportConnectionID](#)
- Using the [TLSEndpointID](#) field of the passed in *TransportOptions*, increment the `ReferenceCount` field of the matching `EndpointID` entry in the TLS Client Management Cluster’s `ProvisionedEndpoints` list.
- Allocate a new [TransportConfigurationStruct](#) associated with the accessing fabric and set the `ConnectionID` and [TransportOptions](#) fields of that struct to the new values.
- Set the [TransportStatus](#) field of the new [TransportConfigurationStruct](#) to `Inactive`.
- Persistently store the resulting [TransportConfigurationStruct](#).
- Update the contents of the [CurrentConnections](#) list attribute to include the new entry.
- If the [TransportOptions](#) field has a non null [ExpiryTime](#) field:
 - Keep track of the time in seconds since allocation for this transport, and once this exceeds the [ExpiryTime](#) the Node SHALL stop any transport for this transport and deallocate it.
- Return the resulting [TransportConfigurationStruct](#) of this allocation in the corresponding [AllocatePushTransportResponse](#) command.

On reboot the Node SHALL restart any transports which were transporting previously.

11.7.9.2. AllocatePushTransportResponse Command

This command SHALL be generated in response to a successful [AllocatePushTransport](#) command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Transport-Configuration	Transport-ConfigurationStruct				M